

D2
N83 I1177

ORIGINAL PAGE IS
OF POOR QUALITY

**THE ROLE OF THE
SHUTTLE REMOTE
MANIPULATOR SYSTEM
IN
SATELLITE SERVICING**



**A PRESENTATION BY SPAR AEROSPACE
JUNE, 1982**

Spar Aerospace Limited
Remote Manipulator Systems Division
1700 Ormont Drive, Weston, Ontario, Canada M9L 2W7

SPAR
**Space &
Electronics Group**

TEL (416) 745-9690

TELEX 065-27360 SPARORM TOR

TWX 610-491-1503

CABLE-SPARORM TOR



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

SRMS BASIC DESCRIPTION

ORIGINAL PAGE IS
OF POOR QUALITY

SRMS SERVICING ROLE

SRMS POTENTIAL GROWTH

UNIVERSAL SERVICE TOOL CONCEPT

11

7-G-320





THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

SRMS SYSTEM

THE SHUTTLE REMOTE MANIPULATOR SYSTEM (SRMS) COMPRISES:

STANDARD CONFIGURATION:

- MANIPULATOR ARM INSTALLED ON PORT LONGERON
- WRIST CCTV CAMERA AND LIGHT
- STANDARD END EFFECTOR (SEE) WITH ELECTRICAL CONNECTOR & EVA HAND HOLD

OPTIONS

- SECOND ARM INSTALLED ON STARBOARD LONGERON
- ELBOW CCTV CAMERA WITH PAN & TILT UNIT
- SPECIAL PURPOSE END EFFECTORS
- SPECIAL PURPOSE GRAPPLE FIXTURES



THE ROLE OF SRMS IN SATELLITE SERVICING



SRMS BASIC DESCRIPTION

SRMS SERVICING ROLE

SRMS POTENTIAL GROWTH


UNIVERSAL SERVICING TOOL CONCEPT




THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR


SRMS TASKS



DEPLOYMENT




RETRIEVAL
/BERTHING




LARGE SPACECRAFT
ASSEMBLY/MODULE
EXCHANGE




REMOTE
SERVICING



ASSIST EVA
SERVICING



SUPPORT OCP
SERVICING



ORIGINAL PAGE IS
OF POOR QUALITY



THE ROLE OF SRMS IN SATELLITE SERVICING



SRMS TASKS

- DEPLOYMENT – 65,000 LB. PAYLOAD BASELINE
- RETRIEVAL
 - 32,000 LB. PAYLOAD BASELINE
 - 65,000 LB. CONTINGENCY CAPABILITY
- SPACECRAFT ASSEMBLY/MODULE EXCHANGE
(Under Evaluation for 25 kW Power System/Power Utilization Package and Space Operations Center)
- SUPPORT ASTRONAUT SERVICING (Baseline for OCP)
- REMOTE SERVICING – USING SRMS SUPPORTED TOOLING



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

DEPLOYMENT


- THE SRMS IS DESIGNED TO DEPLOY AND RELEASE PAYLOADS WITH AN ATTITUDE ACCURACY OF $\pm 5^\circ$ AND A TIP-OFF RATE $< 0.015^\circ/\text{SEC}$. WRT ORBITER.
- A CAPABILITY TO DEPLOY SPINNING PAYLOADS E.G. UNIVERSITY OF IOWA PDP.
- A CAPABILITY TO DEPLOY SATELLITES WITH AN INITIAL VELOCITY UP TO 1 FT/SEC. THIS REQUIRES FURTHER EVALUATION. PRESENT OPERATING CONSTRAINTS NECESSARY TO ENSURE A 2 FT. MAXIMUM STOPPING DISTANCE WOULD ALLOW RELEASE AT TYPICALLY 0.1 FT/SEC. FOR A 32,000 LB. PAYLOAD.



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

TYPICAL ARM CONFIGURATION FOR PAYLOAD RELEASE WITH A ΔV



ORIGINAL PAGE IS
OF POOR QUALITY

7-G-320



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

RETRIEVAL/BERTHING


SRMS WITH THE STANDARD END EFFECTOR CAN INTERFACE MECHANICALLY WITH ANY NON-SPINNING SATELLITE WHICH HAS A COMPATIBLE GRAPPLE FIXTURE. PRESENT CAPTURE CONSTRAINTS FOR RELATIVE TRANSLATIONAL AND ROTATIONAL VELOCITY BETWEEN ORBITER AND SATELLITE ARE 0.1 FT/SEC. AND $\pm 1^\circ$ /SEC. IN ANY AXIS.

- PRESENT GRAPPLE FIXTURES AVAILABLE ARE:
 - STANDARD GRAPPLE FIXTURE – SUITABLE FOR CAPTURE OF A PAYLOAD UP TO 65,000 LB.
 - ELECTRICAL GRAPPLE FIXTURE – CAPABLE OF HANDLING SMALL PAYLOADS.
- GRAPPLE FIXTURES OPTIMIZED FOR SPECIFIC PAYLOADS CAN BE SUPPLIED BY SPAR.
- A SPINNING END EFFECTOR CAPABLE OF DEPLOYING RETRIEVING AND DESPINNING SATELLITES UP TO 16,000 LBS. MASS IS IN THE FEASIBILITY STUDY STAGE AT SPAR.
- BERTHING IS ASSISTED WITH PAYLOAD MARKINGS AND TRUNNION GUIDE MARKINGS. USING GOOD VISUAL CUES ± 1 INCH $\pm 1^\circ$ POSITIONING ACCURACIES CAN BE ACHIEVED.


7-G-320



STANDARD GRAPPLE FIXTURE



ELECTRICAL GRAPPLE FIXTURE



ORIGINAL PAGE IS
OF POOR QUALITY

7-G-320



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

SUPPORT ASTRONAUT SERVICING

- INSPECTION TO ASSESS EVA REQUIREMENTS (TOOLS & EQUIPMENT).
- DEPLOY, MANOEUVRE AND POSITION A WORK STATION
- DEPLOY, MANOEUVRE AND POSITION MODULES FOR FURTHER SERVICING TASKS BY THE ASTRONAUT



REMOTE SERVICING

- INSPECTION.
- REPLACEMENT OF EXPENDED AND FAULTY MODULES.
- REMOVAL AND ATTACHMENT TO REPLENISHMENT EQUIPMENT.
- THE SRMS CAN HANDLE MODULES UNSUITABLE FOR ASTRONAUT HANDLING (SIZE, INERTIA, RADIOACTIVE, ETC.)
- FACILITATED BY SPECIAL END EFFECTOR – PICKED UP BY STANDARD END EFFECTOR
ON ORBIT
– ATTACHED TO SRMS PRIOR TO LAUNCH



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

SRMS BASIC DESCRIPTION

SRMS SERVICING ROLE

SRMS POTENTIAL GROWTH

UNIVERSAL SERVICE TOOL CONCEPT



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

SRMS POTENTIAL GROWTH - INCREASE IN UTILIZATION

DUAL ARM OPERATION

(SRMS is designed to operate 2 arms in series)

- MAXIMIZE UTILIZATION OF EXISTING HARDWARE

REMOTE MOUNTED SRMS

- SPACE OPERATIONS CENTRE APPLICATIONS

AV PAYLOAD DEPLOYMENT

- MEET VOL XIV SATELLITE DEPLOYMENT REQUIREMENTS WITHOUT USING SPACECRAFT OR ORBITER CONSUMABLES

SPIN/DESPIN RETRIEVAL/DEPLOYMENT (Currently under study at SPAR)

- PROVIDE STANDARD END EFFECTOR WITH A "SPIN" JOINT OR A SPECIAL PURPOSE END EFFECTOR

UNIVERSAL SERVICE TOOL

- PROVIDE A BASIC REMOTE SERVICING CAPABILITY



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

POTENTIAL SRMS GROWTH – PERFORMANCE IMPROVEMENTS

IMPROVED POSITIONING ACCURACY

- INCORPORATE SOFTWARE FOR INTERFACE WITH PHOTOGRAMMETRY HARDWARE WHICH USES WRIST OR ORBITER CAMERAS TO PROVIDE OPERATOR WITH RELATIVE POSITION AND RATE DATA.

IMPROVE SRMS/PAYLOAD ELECTRICAL INTERFACE

- MODIFY STANDARD END EFFECTOR WITH AN "ACTIVE" ELECTRICAL CONNECTOR TO INCREASE NUMBER OF SIGNALS ACCOMMODATED ON PAYLOAD/SRMS ELECTRICAL INTERFACE.

ADDITION OF AN UPPER ARM ROLL JOINT

- ELIMINATE PRESENT SINGULARITIES IMPROVE OBSTACLE CLEARANCE CAPABILITY INCREASE/IMPROVE REACH.

END POINT FORCE SENSING/ FEEDBACK (Currently under investigation at SPAR)

- IMPROVE HANDLING PRECISION



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

SPECIAL PURPOSE END EFFECTOR APPLICATIONS

- DEPLOYMENT AND RETRIEVAL
 - STABLE NON-SPINNERS
 - STABLE SPINNERS
 - UNSTABLE/UNCO-OPERATIVE
 - DEBRIS COLLECTORS
- SPECIAL HANDLING
 - SPECIFIC SHAPES OR STRUCTURE
 - IRREGULAR, HOLLOW, CONVEX, CONCAVE
- PAYLOAD SERVICING
 - LATCHING/DELATCHING
 - TORQUING (WRENCH, SCREW DRIVER)
 - ROTARY/POWER TOOLS (CUTTER, DRILL)
 - REPLENISHMENT OPERATIONS



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

SRMS BASIC DESCRIPTION

SRMS SERVICING ROLE

SRMS POTENTIAL GROWTH

UNIVERSAL SERVICE TOOL CONCEPT



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

UNIVERSAL SERVICE TOOL SYSTEM (USTS) FOR ON-ORBIT SPACE SYSTEM SERVICING


- A VERSATILE SERVICE TOOL SYSTEM:
 - MODULAR DESIGN ACCOMMODATING SIMPLE CHANGE-OUT TOOLS, MANIPULATOR AND OPERATOR INTERFACES
 - VARIABLE TORQUE CAPABILITY
- A MODE OF OPERATION FOR SRMS REMOTE SERVICING (USING SPEE CONNECTOR FOR ELECTRICAL POWER AND CONTROL INTERFACING).
- A MODE OF OPERATION FOR ASTRONAUT EVA (MANUAL OPERATION OF TOOL AND LATCH DRIVES AND TOOL INTERCHANGE).
- MINIMUM PAYLOAD INTERFACE ENVELOPE
- WEIGHT EFFECTIVE DESIGN.



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

UNIVERSAL SERVICE TOOL SYSTEM




ORIGINAL PAGE IS
OF POOR QUALITY

7-G-320



UNIVERSAL SERVICE TOOL SYSTEM (USTS) CONCEPT



ORIGINAL PAGE IS
OF POOR QUALITY

7-G-320

PATENT APPLIED FOR



THE ROLE OF SRMS IN SATELLITE SERVICING

SPAR

CONCLUDING REMARKS

- SRMS IS THE BASELINE ORBITER PAYLOAD DEPLOYMENT AND RETRIEVAL SYSTEM.
- SRMS HAS A GROWTH POTENTIAL TO SUPPORT SERVICING TASKS AS REQUIREMENTS EVOLVE.
- SRMS GROWTH FOR SATELLITE SERVICING IS GENERALLY BY ADD-ON KIT (E.G. SPECIAL END EFFECTORS).

ORIGINAL PAGE IS
OF POOR QUALITY

7-G-320